**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# FLUSH NON-ILLUMINATED PUSHBUTTON

Flush Head

L21CA01
Pushbutton Flush Latching Red



- IP66 / IP69K
- Spring return or latching
- Optional text or symbol

### PRODUCT DESCRIPTION

Standard flush pushbutton heads that mount in a 22.5mm hole with protection rating IP66 / IP69K
Combine with separate clip and contact blocks to make complete pushbutton assembly.
Available in multiple colours in spring return or latching.
Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L21xxxx to L22xxxx.
Optional text or symbol can be added please enquire for more details.

## TECHNICAL DATA

| | |
|---|---|
| **Approvals** | UL 508, CSA 22.2, BV, CB, CE |
| **Climatic resistance - constant humid heat** | IEC 60068-2-3 |
| **Climatic resistance - cyclic damp heat** | IEC 60068-2-30 |
| **Climatic resistance - sea air** | IEC 60068-2-52 |
| **Colour** | Red |
| **Function** | Latching |
| **Illuminated** | No |
| **Impact resistance** | IK05 |
| **IP class** | IP66, IP69, IP69K |
| **Lens colour** | Red |
| **Mechanical life expectancy** | 500 000 cycles |
| **Protection class** | II (double insulated) |
| **Recommended tightening torque** | 3 |
| **Storage temperature max** | 70 °C |

| | |
|---|---|
| **Storage temperature min** | -40 °C |
| **Temperature operational max** | 70 °C |
| **Temperature operational min** | -25 °C |
| **Type** | Flush pushbutton |
| **Weight** | 15.8 g |

