

**NON-FLUSH NON-ILLUMINATED
PUSHBUTTON**

Non Flush Head

L21CB03
Pushbutton Non Flush Latching Black

- IP66 / IP69K
- Spring return or latching
- Optional text or symbol

**PRODUCT DESCRIPTION**

Non flush (projecting) pushbutton heads that mount in a 22.5mm hole with protection rating IP66 / IP69K

Ideal for applications where an easier activation is required for example when wearing gloves.

Combine with separate clip and contact blocks to make complete pushbutton assembly.

Available in multiple colours in spring return or latching.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

Optional text or symbol can be added please enquire for more details.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Black
Function	Latching
Illuminated	No
Impact resistance	IK05
IP class	IP66, IP69, IP69K
Mechanical life expectancy	500 000 cycles
Protection class	II (double insulated)
Recommended tightening torque	3
Storage temperature max	70 °C

Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Type	Non flush pushbutton
Weight	15.8 g

