OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

FLUSH ILLUMINATED PUSHBUTTON

Flush Head

L21AH10
Pushbutton Illuminated Flush Spring Return Red



- IP66 / IP69K
- Spring return or latching
- Optional text or symbol
- Illuminate with LED blocks

PRODUCT DESCRIPTION

Standard illuminated flush pushbutton heads that mount in a 22.5mm hole with protection rating IP66 / IP69K
Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated pushbutton assembly.
Available in multiple colours in spring return or latching.
Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L21xxxx to L22xxxx.
Optional text or symbol can be added please enquire for more details.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Red
Function	Spring return
Illuminated	Yes
Impact resistance	IK05
IP class	IP66, IP69, IP69K
Lens colour	Red
Mechanical life expectancy	5 000 000 cycles
Protection class	II (double insulated)
Protection rating front of panel	IP69K

Recommended tightening torque	3
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Type	Flush pushbutton
Weight	15.8 g

