

SUPER FLUSH ILLUMINATED PUSHBUTTON

Super Flush Head

L23AH50

Pushbutton Illuminated Super Flush Spring Return
White

- IP66 / IP69K
- Spring return
- Low profile flush mount
- Illuminate with LED blocks



PRODUCT DESCRIPTION

Illuminated super flush pushbutton heads that mount in a 30.5mm hole with protection rating IP66 / IP69K

Ideal for applications where a tamper proof, low profile button is required as only protrudes from front of panel by 2.8mm.

Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated pushbutton assembly.

Available in multiple colours in spring return with a metallic chrome bezel.

Optional text or symbol can be added please enquire for more details.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	White
Function	Spring return
Illuminated	Yes
Impact resistance	IK05
IP class	IP66
Mechanical life expectancy	5 000 000 cycles
Recommended tightening torque	3
Storage temperature max	70 °C

Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Type	Super flush pushbutton



