

## FLUSH ILLUMINATED PUSHBUTTON

Flush Head

L21CH40

Pushbutton Illuminated Flush Latching Yellow

- IP66 / IP69K
- Spring return or latching
- Optional text or symbol
- Illuminate with LED blocks



### PRODUCT DESCRIPTION

Standard illuminated flush pushbutton heads that mount in a 22.5mm hole with protection rating IP66 / IP69K

Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated pushbutton assembly.

Available in multiple colours in spring return or latching.

Supplied with a matt chrome bezel as standard.

For black plastic bezel change the part number from L21xxxx to L22xxxx.

Optional text or symbol can be added please enquire for more details.

### TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Yellow
Function	Latching
Illuminated	Yes
Impact resistance	IK05
IP class	IP66, IP69, IP69K
Lens colour	Yellow
Mechanical life expectancy	500 000 cycles
Protection class	II (double insulated)
Protection rating front of panel	IP69K

<b>Recommended tightening torque</b>	3
<b>Storage temperature max</b>	70 °C
<b>Storage temperature min</b>	-40 °C
<b>Temperature operational max</b>	70 °C
<b>Temperature operational min</b>	-25 °C
<b>Type</b>	Flush pushbutton
<b>Weight</b>	15.8 g

