0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **ILLUMINATED MUSHROOM HEADS**

Illuminated

L22DM40 Mushroom Head Illuminated Dia. 40mm Pull Reset

- IP66 / IP69K
- Head size Ø32mm or Ø40mm
- Pull or turn reset
- Illuminate with LED blocks





## PRODUCT DESCRIPTION

Illuminated, latching mushroom heads that mount in a 22.5mm hole with protection rating IP66 / IP69K

Available in head sizes Ø32mm & Ø40mm with reset options of pull & turn release.

Combine with separate 3 module clip, LED block (must be in centre position) and contact blocks to make a complete illuminated mushroom head assembly.

## **TECHNICAL DATA**

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Yellow
Function	Pull to reset
Illuminated	Yes
Impact resistance	IK05
IP class	IP66, IP69, IP69K
Mechanical life expectancy	150 000 cycles
Recommended tightening torque	3
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C

