OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ILLUMINATED MUSHROOM HEADS

Illuminated

L22DM50
Mushroom Head Illuminated Dia. 40mm Pull Reset
White



- IP66 / IP69K
- Head size Ø32mm or Ø40mm
- Pull or turn reset
- Illuminate with LED blocks

PRODUCT DESCRIPTION

Illuminated, latching mushroom heads that mount in a 22.5mm hole with protection rating IP66 / IP69K

Available in head sizes Ø32mm & Ø40mm with reset options of pull & turn release.

Combine with separate 3 module clip, LED block (must be in centre position) and contact blocks to make a complete illuminated mushroom head assembly.

TECHNICAL DATA

Type	Mushroom ø40mm
Function	Pull to reset
Colour	White
Illuminated	Yes

IP class	IP66, IP69, IP69K
Impact resistance	IK05
Temperature operational min	-25 °C
Temperature operational max	70 °C
Storage temperature min	-40 °C
Storage temperature max	70 °C
Mechanical life expectancy	150 000 cycles
Approvals	UL 508, CSA 22.2, BV, CB, CE
Recommended tightening torque	3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52

Climatic resistance - constant humid heat	IEC 60068-2-3

