

NON-ILLUMINATED TWIN TOUCH FLUSH

Non Illuminated

L61QA22

Twintouch Flush Green Arrows Open Close

- IP66
- Flush pushbuttons
- Spring return
- Various colours & symbols



PRODUCT DESCRIPTION

Non illuminated flush twin touch heads that mount in a 22.5mm hole with protection rating IP66

Combine with separate 333E clip and contact blocks to make complete twin touch assembly.
Available in various colour / text / symbol combinations.
All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Green / green
Function	Spring return
Illuminated	No
Impact resistance	IK05
IP class	IP66

Mechanical life expectancy	5 000 000 cycles
Recommended tightening torque	3
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Type	Twin touch flush

