OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

MECHANICAL RESET BUTTON

Adjustable mechanical push button

L21HA06
Pushbutton Adjustable Mechanical Reset Blue



- Flush or non flush
- Stroke 11mm
- Adjustment 26mm to 46mm depth
- Optional engraving possible

PRODUCT DESCRIPTION

Adjustable push button that allows mechanical activation of other devices.
The buttons are available in 6 colours in flush or non flush.
When pressed the button has a movement stroke of 11mm and the rear plunger can be adjusted between 26mm to 46mm from the front side of the panel.
Optionally any of the heads can be supplied with custom text or symbol please enquire for further details.

TECHNICAL DATA

Type	Flush pushbutton
Function	Spring return
Colour	Blue
Illuminated	No

IP class	IP65
Impact resistance	IK05
Protection class	II (double insulated)
Temperature operational min	-25 °C
Temperature operational max	70 °C
Storage temperature min	-40 °C
Storage temperature max	70 °C
Mechanical life expectancy	500 000 cycles
Height	20.8 mm
Weight	24 g
Approvals	UL 508, CSA 22.2, BV, CB, CE
Tightening torque max	3
Recommended tightening torque	3

Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Climatic resistance - constant humid heat	IEC 60068-2-3

