

MECHANICAL RESET BUTTON

Adjustable mechanical push button

L21HB01

Pushbutton Adjustable Mechanical Reset Non Flush
Red



- Flush or non flush
- Stroke 11mm
- Adjustment 26mm to 46mm depth
- Optional engraving possible

PRODUCT DESCRIPTION

Adjustable push button that allows mechanical activation of other devices.

The buttons are available in 6 colours in flush or non flush.

When pressed the button has a movement stroke of 11mm and the rear plunger can be adjusted between 26mm to 46mm from the front side of the panel.

Optionally any of the heads can be supplied with custom text or symbol please enquire for further details.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Red
Function	Spring return
Height	20.8 mm
Illuminated	No
Impact resistance	IK05
IP class	IP65
Recommended tightening torque	3
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Tightening torque max	3
Type	Non flush pushbutton

Weight

18 g

