OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SHORT HANDLE NON-ILLUMINATED SELECTOR SWITCH

Short Lever Handle

L21KC03
Selector Handle 2 Position Stable 45° Black



- IP66 / IP69K
- 2 or 3 position
- Latching or spring return
- Optional lever colours

PRODUCT DESCRIPTION

Non illuminated selector switch head with a short lever handle that mount in a 22.5mm hole with protection rating IP66 / IP69K
Combine with separate clip and contact blocks to make complete switch assembly.

Standard body colour is grey with a black lever but also available with red, green & grey lever please enquire for more details.

Available in 2 or 3 position, latching or spring return in various switching angles.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L21xxxx to L22xxxx.

TECHNICAL DATA

Type	Short lever
Positions	2
Angle	45°
Function	Stable
Colour	Black
Illuminated	No

IP class	IP66, IP69, IP69K
Impact resistance	IK05
Protection class	II (double insulated)
Temperature operational min	-25 °C
Temperature operational max	70 °C
Storage temperature min	-40 °C
Storage temperature max	70 °C

Mechanical life expectancy	300 000 cycles
Weight	17.8 g
Approvals	UL 508, CSA 22.2, BV, CB, CE
Recommended tightening torque	3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Climatic resistance - constant humid heat	IEC 60068-2-3



