OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

KEY HANDLE NON-ILLUMINATED SELECTOR SWITCH

Key Handle

L21LB00
Selector Key 2 Position Spring Return 45° Black 455



- IP66 / IP69K
- 2 or 3 position
- Latching or spring return
- Multiple key profile options

PRODUCT DESCRIPTION

Non illuminated selector switch head that is key operated and mounts in a 22.5mm hole with protection rating IP66 / IP69K
Combine with separate clip and contact blocks to make complete switch assembly.

Each head supplied with 2 x keys.
Key profile 455 is standard.
Key profile 1424A available at no extra cost.
Other key profiles available at additional cost please enquire for details.

Available in 2 or 3 position, latching or spring return in various switching angles and key free options.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L21xxxx to L22xxxx.

TECHNICAL DATA

Type	Key
Positions	2
Angle	45°
Function	Spring return
Key removable	0
Colour	Black
Illuminated	No

IP class	IP66, IP69, IP69K
Impact resistance	IK05

Protection class	II (double insulated)
Temperature operational min	-25 °C
Temperature operational max	70 °C
Storage temperature min	-40 °C
Storage temperature max	70 °C
Mechanical life expectancy	300 000 cycles
Weight	31.2 g
Approvals	UL 508, CSA 22.2, BV, CB, CE
Recommended tightening torque	3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Climatic resistance - constant humid heat	IEC 60068-2-3







