OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SHORT HANDLE ILLUMINATED SELECTOR SWITCH

Short Lever Handle

L21MF30
Selector Handle Illuminated 3 Pos Spring Ret 45° Black



- IP66 / IP69K
- 2 or 3 position
- Illuminate with LED blocks
- Red, green or black lever with translucent surround

PRODUCT DESCRIPTION

Illuminated selector switch head with a short lever handle that mount in a 22.5mm hole with protection rating IP66 / IP69K
Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated selector switch assembly.

The central part of the switch head, side and tip of the lever are translucent and illuminate according to the colour of LED block used.
The lever of the switch is solid in colour and available in red, green & black.

Available in 2 or 3 position, latching or spring return in various switching angles.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L21xxxx to L22xxxx.

TECHNICAL DATA

Type	Short lever
Positions	3
Angle	45°
Function	Spring return
Colour	Black
Illuminated	Yes

IP class	IP66, IP69, IP69K
Impact resistance	IK05
Protection class	II (double insulated)
Temperature operational min	-25 °C
Temperature operational max	70 °C
Storage temperature min	-40 °C

Storage temperature max	70 °C
Mechanical life expectancy	300 000 cycles
Weight	17.8 g
Approvals	UL 508, CSA 22.2, BV, CB, CE
Recommended tightening torque	3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Climatic resistance - constant humid heat	IEC 60068-2-3





