**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# SHORT HANDLE ILLUMINATED SELECTOR SWITCH

Short Lever Handle

L21MH30
Selector Handle Illuminated 3 Pos Spring Ret 45° Black



- IP66 / IP69K
- 2 or 3 position
- Illuminate with LED blocks
- Red, green or black lever with translucent surround

### PRODUCT DESCRIPTION

Illuminated selector switch head with a short lever handle that mount in a 22.5mm hole with protection rating IP66 / IP69K
Combine with clip, contact blocks and LED module (must be in centre position) to make complete illuminated selector switch assembly.

The central part of the switch head, side and tip of the lever are translucent and illuminate according to the colour of LED block used.
The lever of the switch is solid in colour and available in red, green & black.

Available in 2 or 3 position, latching or spring return in various switching angles.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L21xxxx to L22xxxx.

# TECHNICAL DATA

| | |
|---|---|
| **Type** | Short lever |
| **Positions** | 3 |
| **Angle** | 45° |
| **Function** | Spring return |
| **Colour** | Black |
| **Illuminated** | Yes |

| | |
|---|---|
| **IP class** | IP66, IP69, IP69K |
| **Impact resistance** | IK05 |
| **Protection class** | II (double insulated) |
| **Temperature operational min** | -25 °C |
| **Temperature operational max** | 70 °C |
| **Storage temperature min** | -40 °C |

| | |
|---|---|
| **Storage temperature max** | 70 °C |
| **Mechanical life expectancy** | 300 000 cycles |
| **Weight** | 17.8 g |
| **Approvals** | UL 508, CSA 22.2, BV, CB, CE |
| **Recommended tightening torque** | 3 |
| **Climatic resistance - cyclic damp heat** | IEC 60068-2-30 |
| **Climatic resistance - sea air** | IEC 60068-2-52 |
| **Climatic resistance - constant humid heat** | IEC 60068-2-3 |







