OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SCREW LED BLOCKS

Screw terminals

33EAGM
LED Block Screw 130V ac Green



- Long lifetime upto 100,000 hours
- 5 colour & voltage options
- Finger safe IP20 terminals

PRODUCT DESCRIPTION

LED blocks with screw terminal connection that snap directly in the centre position of 1, 3 or 5 position clips.
Suitable for all illuminated pushbutton, selector switch, mushroom or pilot light heads.
Available in colour options, red, green, yellow, white & blue.
Available in voltage options 12-24Vac/dc, 48Vac/dc, 110Vdc, 130Vac & 230Vac.
Long lifetime of up to 100,000 hours.

TECHNICAL DATA

Colour	Green
Connection type	Screw
LED supply voltage	130V AC
LED voltage tolerance	± 10%

Rated insulation voltage Ui	300 V

Protection rating rear of panel	IP20
Connection stranded wire with ferrule min	0.5 mm²
Connection stranded wire with ferrule max	1.5 mm²
Connection solid wire max	2.5 mm²
Temperature operational min	-25 °C
Temperature operational max	70 °C
Storage temperature min	-40 °C

Storage temperature max	70 °C
Lifetime at rated supply voltage (25°C)	50000 h
Weight	17 g
Approvals	UL 508, CSA 22.2, BV, CB, CE
Tightening torque max	1.2
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Climatic resistance - constant humid heat	IEC 60068-2-3
Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3)	4 kV
Current consumption	20 mA ±10%
Frequency	50/60 Hz





