OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

PUSH-IN LED BLOCKS

Push in screwless terminals

33RAYH
LED Block Push 230V ac Yellow



- Quick connection with no tools required
- Long lifetime up to 100,000 hours
- 5 colour & 3 voltage options
- Finger safe IP20 terminals

PRODUCT DESCRIPTION

LED blocks with push in screwless terminals offer a fast and secure connection method.
Snap directly in the centre position of 1, 3 or 5 position clips.
Suitable for all illuminated pushbutton, selector switch, mushroom or pilot light heads.
Available in colour options, red, green, yellow, white & blue.
Available in voltage options 12-24Vac/dc, 130Vac & 230Vac.
Long lifetime of up to 100,000 hours.

TECHNICAL DATA

Colour	Yellow
Connection type	Push In
LED supply voltage	230V AC
LED voltage tolerance	± 30%

Rated insulation voltage Ui	300 V

Protection rating rear of panel	IP20
Connection stranded wire with ferrule min	0.5 mm²
Connection stranded wire with ferrule max	1.5 mm²
Connection solid wire max	2.5 mm²
Temperature operational min	-25 °C

Temperature operational max	70 °C
Storage temperature min	-40 °C
Storage temperature max	70 °C
Lifetime at rated supply voltage (25°C)	100000 h
Weight	19 g
Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Climatic resistance - constant humid heat	IEC 60068-2-3
Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3)	4 kV
Current consumption	16 mA ±30%
Frequency	50/60 Hz



