

FASTON LED BLOCKS

Faston flat blade terminals

33DARL

LED Block Faston 24V ac/dc Red

- Accepts spade crimp terminals
- Faston 6.35mm or 2 x 2.8mm
- Long lifetime up to 100,000 hours
- 5 colour & 3 voltage options



PRODUCT DESCRIPTION

LED blocks with Faston flat blade terminals offer a fast and secure connection method.

Use with Faston 6.35mm or 2 x 2.8mm spade crimp terminals.

Snap directly in the centre position of 1, 3 or 5 position clips.

Suitable for all illuminated pushbutton, selector switch, mushroom or pilot light heads.

Available in colour options, red, green, yellow, white & blue.

Available in voltage options 12-24Vac/dc, 130Vac & 230Vac.

Long lifetime of up to 100,000 hours.

TECHNICAL DATA

| | |
|--|------------------------------|
| Approvals | UL 508, CSA 22.2, BV, CB, CE |
| Climatic resistance - constant humid heat | IEC 60068-2-3 |
| Climatic resistance - cyclic damp heat | IEC 60068-2-30 |
| Climatic resistance - sea air | IEC 60068-2-52 |
| Colour | Red |
| Connection type | Faston |
| Current consumption | 25 mA \pm 20% |
| Faston size | 6.35mm / 2 x 2.8mm |
| Frequency | 50/60 Hz |
| LED supply voltage | 12-24V AC/DC |

| | |
|---|----------|
| LED voltage tolerance | ± 20% |
| Lifetime at rated supply voltage (25°C) | 100000 h |
| Protection rating rear of panel | IP20 |
| Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3) | 4 kV |
| Rated insulation voltage Ui | 300 V |
| Storage temperature max | 70 °C |
| Storage temperature min | -40 °C |
| Temperature operational max | 70 °C |
| Temperature operational min | -25 °C |
| Weight | 17 g |

