OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

FASTON LED BLOCKS

Faston flat blade terminals

33DAGH
LED Block Faston 230V ac Green



- Accepts spade crimp terminals
- Faston 6.35mm or 2 x 2.8mm
- Long lifetime up to 100,000 hours
- 5 colour & 3 voltage options

PRODUCT DESCRIPTION

LED blocks with Faston flat blade terminals offer a fast and secure connection method.
Use with Faston 6.35mm or 2 x 2.8mm spade crimp terminals.
Snap directly in the centre position of 1, 3 or 5 position clips.
Suitable for all illuminated pushbutton, selector switch, mushroom or pilot light heads.
Available in colour options, red, green, yellow, white & blue.
Available in voltage options 12-24Vac/dc, 130Vac & 230Vac.
Long lifetime of up to 100,000 hours.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Green
Connection type	Faston
Current consumption	16 mA ±30%
Faston size	6.35mm / 2 x 2.8mm
Frequency	50/60 Hz
LED supply voltage	230V AC

LED voltage tolerance	± 30%
Lifetime at rated supply voltage (25°C)	50000 h
Protection rating rear of panel	IP20
Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3)	4 kV
Rated insulation voltage Ui	300 V
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Weight	17 g





