

## CONTROL BOXES, COMPLETE

LBX10610

Box Pushbutton Red "O" 1 x N/C



### PRODUCT DESCRIPTION

Enclosures fitted with different functions.

The coated enclosures we present here are a few standard models, and a very small part of what is available. When it comes to coated enclosures and its features, they differ greatly from application to application. We have therefore specialized in customizing enclosures in the Baco range. Everything from smaller to large series.

We customize everything from the various combinations of pushbuttons, knobs, emergency stops, etc., to also arrange special texts or symbols on the enclosure or buttons.

Contact us for more information on this and we will help you to get a good solution.

Of course, it is also easy to order loose parts and assemble them yourself.

### TECHNICAL DATA

|   |                              |
|---|------------------------------|
| Approvals                                 | UL 508, CSA 22.2, BV, CB, CE |
| Cable entry                               | 2xM16/M20                    |
| Climatic resistance - constant humid heat | IEC 60068-2-3                |
| Climatic resistance - cyclic damp heat    | IEC 60068-2-30               |
| Climatic resistance - sea air             | IEC 60068-2-52               |
| Colour                                    | Red                          |
| Contact type                              | 1 x N/C                      |
| Enclosure colour                          | Grey, Black                  |
| Impact resistance                         | IK05, IK07                   |
| IP class                                  | IP66                         |

|                             |        |
|-----------------------------|--------|
| Storage temperature max     | 70 °C  |
| Storage temperature min     | -40 °C |
| Temperature operational max | 70 °C  |
| Temperature operational min | -25 °C |

● Red

NC

