

CONTROL BOXES, COMPLETE

LBX12610

Box Selector Key 1 x N/O



PRODUCT DESCRIPTION

Enclosures fitted with different functions.

The coated enclosures we present here are a few standard models, and a very small part of what is available. When it comes to coated enclosures and its features, they differ greatly from application to application. We have therefore specialized in customizing enclosures in the Baco range. Everything from smaller to large series.

We customize everything from the various combinations of pushbuttons, knobs, emergency stops, etc., to also arrange special texts or symbols on the enclosure or buttons.

Contact us for more information on this and we will help you to get a good solution.

Of course, it is also easy to order loose parts and assemble them yourself.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Cable entry	2xM16/M20
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Contact type	1 x N/O
Enclosure colour	Grey, Black
Impact resistance	IK05, IK07
IP class	IP66
Storage temperature max	70 °C

Storage temperature min -40 °C

Temperature operational max 70 °C

Temperature operational min -25 °C

● Black

NO

13 14

