**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# KEY HANDLE NON-ILLUMINATED SELECTOR SWITCH

Key Handle

L21LK00
Selector Key 2 Position Stable 90° Black 455



- IP66 / IP69K
- 2 or 3 position
- Latching or spring return
- Multiple key profile options

### PRODUCT DESCRIPTION

Non illuminated selector switch head that is key operated and mounts in a 22.5mm hole with protection rating IP66 / IP69K
Combine with separate clip and contact blocks to make complete switch assembly.

Each head supplied with 2 x keys.
Key profile 455 is standard.
Key profile 1424A available at no extra cost.
Other key profiles available at additional cost please enquire for details.

Available in 2 or 3 position, latching or spring return in various switching angles and key free options.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L21xxxx to L22xxxx.

## TECHNICAL DATA

| | |
|---|---|
| **Type** | Key |
| **Positions** | 2 |
| **Angle** | 90° |
| **Function** | Stable |
| **Key removable** | 1 |
| **Colour** | Black |
| **Illuminated** | No |

| | |
|---|---|
| **IP class** | IP66, IP69, IP69K |
| **Impact resistance** | IK05 |

| | |
|---|---|
| **Protection class** | II (double insulated) |
| **Temperature operational min** | -25 °C |
| **Temperature operational max** | 70 °C |
| **Storage temperature min** | -40 °C |
| **Storage temperature max** | 70 °C |
| **Mechanical life expectancy** | 300 000 cycles |
| **Weight** | 31.2 g |
| **Approvals** | UL 508, CSA 22.2, BV, CB, CE |
| **Recommended tightening torque** | 3 |
| **Climatic resistance - cyclic damp heat** | IEC 60068-2-30 |
| **Climatic resistance - sea air** | IEC 60068-2-52 |
| **Climatic resistance - constant humid heat** | IEC 60068-2-3 |









