

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

BRASS EARTH DISTRIBUTION TERMINALS

MRS

MRS1501 MRS 9 x 6 Threaded copper bar 1m

- Screws in galvanized steel.
- · High conductivity brass
- · Complete with fixings
- · Earthing Bars





PRODUCT DESCRIPTION

Teknomegas earthing and neutral terminals offer lengths and connections.

The brass earth and neutral terminals comes in 1-meter lengths which can be cut down to suit an application.

With the various versions, Teknomega have designed holes at the end of the terminals making it easier to fix on to boards.


Double earthing terminals offers a double connection with blind holes which can have a cable lug up to 95mm².

The terminal supports are made manufactured in polyamide 66 self-extinguishing V2-UL94.

TECHNICAL DATA

DIMENSIONS

Height	9 mm
Number of holes/diameter	5.2
Number of holes	113
Bar width	6 mm
Weight	0.38 kg



Code	Reference	Weight (Kg)	A (mm)	B (mm)	М	Ø holes (mm)	n° holes	Stripped wire (mm²)	Wire with ferrule (mm²)	(Nm)
MRS1501	MRS 9x6	0,380	9	6	M4	5,2	113	2,5 + 6	1,5 = 6	2
MRS1506	MRS 12x8	0,774	12	8	M5	6,5	116	2,5 + 16	1,5 + 10	3