

BRASS EARTH DISTRIBUTION TERMINALS

MRS

MRS3005
MRS 2x12

- Screws in galvanized steel.
- High conductivity brass
- Complete with fixings
- Earthing Bars



PRODUCT DESCRIPTION

Teknomegas earthing and neutral terminals offer lengths and connections.

The brass earth and neutral terminals comes in 1-meter lengths which can be cut down to suit an application.

With the various versions, Teknomega have designed holes at the end of the terminals making it easier to fix on to boards.


Double earthing terminals offers a double connection with blind holes which can have a cable lug up to 95mm².

The terminal supports are made manufactured in polyamide 66 self-extinguishing V2-UL94.

TECHNICAL DATA

DIMENSIONS

Height	9 mm
Number of holes/diameter	5.5
Number of holes	12
Bar width	19 mm
Weight	0.215 kg



Code	Reference	Weight (Kg)	L (mm)	L1 (mm)	A (mm)	B (mm)	Ø holes (mm)	n° holes	Stripped wire (mm²)	Wire with ferrule (mm²)
MRS3000	MRS 2x6	0.17	102	50	9	19	5.5	6	2.5 + 6	1.5 + 6.2
MRS3005	MRS 2x12	0.215	144	50	9	19	5.5	12	2.5 + 6	1.5 + 6.2
MRS3010	MRS 2x24	0.326	230	120	9	19	5.5	24	2.5 + 6	1.5 + 6.2