

4 POLE DISTRIBUTION BLOCKS

RPQ

RPQ2017

Specific tool for RPQ1017 - RPN160-14

- 40 A to 160 A
- Brass conductors
- Self-extinguishing insulating structure UL 94-V0
- Insulation between phases



PRODUCT DESCRIPTION

The 4 pole distribution blocks are brass conductors which have galvanized steel screws included this enables insulation between phases.

Each block has a front removable protection screen. With self-extinguishing insulating structure :

UL 94-V0 approved

Quick hook-up on DIN rails.

Compliant with standards IEC 947-7-1.

Advantages

- Separate inputs
- Forged conductors
- Easy wiring: RPQ1015, RPQ1018
- Modular depth: RPQ1016, RPQ1017

TECHNICAL DATA

GENERAL DATA

Rated current	160 A
IP class	IP20
Nominal insulation voltage	600 V
Short-circuit current resistance IPK (peak value)	22 kA
Short-circuit current resistance ICW over 1s	9 kA

CONNECTION DATA

Connections	14
Number of outputs A	4
Output A: diameter	8.5 mm
Output A: wire cross-section stranded, min.	10 mm ²

Output A: wire cross-section stranded, max.	35 mm ²
Output A: wire cross-section stranded with wire-end ferrules, min.	10 mm ²
Output A: wire cross-section stranded with wire-end ferrules, max.	16 mm ²
Output A: torque, min.	2
Output A: torque, max.	3
Number of outputs B	10
Output B: diameter	7 mm
Output B: wire cross-section stranded, min.	2.5 mm ²
Output B: wire cross-section stranded, max.	16
Output B: wire cross-section stranded with wire-end ferrules, min.	1.5 mm ²
Output B: wire cross-section stranded with wire-end ferrules, max.	16 mm ²
Output B: torque, min.	2
Output B: torque, max.	3
Screw type	Galvanized steel screws

DIMENSIONS

Length (L)	161 mm
Height (H)	27 mm
Width (P)	17 mm
Width (I)	57 mm

ADDITIONAL DATA

Pack size	1
-----------	---