

COMPACT MODULAR DISTRIBUTION TERMINALS - SVBKA

SVBKA

27210.5
SVBKA 95 BU

- IP20 protection
- Wire connection cross sections 1.5 - 240 mm²
- Suitable for copper and aluminium cables
- Foot can be snapped on DIN 35 or direct mounted
- Housing made of polyamide 6.6 UL 94 V-0



PRODUCT DESCRIPTION

The SVBKA screw-distributor block makes it possible to distribute potential and power in a compact space without any additional accessories. The SVBKA blocks can be used with aluminum and copper cables from 1.5 to 240 mm². They can be used in installation and distribution board construction and also in controller construction for machinery. The SVBKA blocks are mounted by snapping them on to TS 35 DIN rails. They can also be attached directly to a mounting plate using the screw flange located on the side of the housing.

The SVBKA screw-distributor blocks guarantee IP20 protection, even when you are connecting larger conductor cross-sections. For smaller cable cross-sections, finger safety is ensured by the BS-SVBKA covers (available as accessory).

TECHNICAL DATA

GENERAL DATA

Rated current copper	250 A
Rated current aluminium	220 A
Rated voltage V AC	1000 V AC
Rated voltage V DC	1000 V DC
Mounting	TS 35 and direct mount
Overvoltage category	III
Contamination degree	3
Colour	Blue
IP class	IP20

CONNECTION DATA

Connections	2
-------------	---

Number of inputs A	1
Input A: rated cross-section	95 mm ²
Input A: wire cross-section rigid, min.	6 mm ²
Input A: wire cross-section rigid, max.	95 mm ²
Input A: wire cross-section stranded, min.	6 mm ²
Input A: wire cross-section stranded, max.	70 mm ²
Input A: wire cross-section with wire-end ferrules, min.	6 mm ²
Input A: wire cross-section with wire-end ferrules, max.	70 mm ²
Input A: stripping length	20 mm
Input A: screw head	Allen key
Input A: torque, min.	12
Input A: torque, max.	22
Number of outputs A	1
Output A: rated cross-section	95 mm ²
Output A: wire cross-section rigid, min.	6 mm ²
Output A: wire cross-section rigid, max.	95 mm ²
Output A: wire cross-section stranded, min.	6 mm ²
Output A: wire cross-section stranded, max.	70 mm ²
Output A: wire cross-section stranded with wire-end ferrules, min.	6 mm ²
Output A: wire cross-section stranded with wire-end ferrules, max.	70 mm ²
Output A: stripping length	20 mm
Output A: screw head	Allen key
Output A: torque, min.	12
Output A: torque, max.	22

DIMENSIONS

Length	85 mm
Height	51 mm
Height TS 35/7.5	54 mm
Width	24.8 mm

MATERIALS

Insulation material	Polyamide 6.6
---------------------	---------------

Flammability class	UL94-V0
Operating temperature to	120 °C
Operating temperature from	-40 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	EEC
Weight	65 g
Pack size	10