

INTERCON-1 USB3.0 CABLES

B3PMBT-3.0-PA

USB 3.0 cable, static, horizontal screw, B to A, 3mtr

- Supports high data rate transfers up to 5 Gbps
- InfiniFlex robot cable
- Thumbscrew locking



PRODUCT DESCRIPTION

USB 3.0 also known as Superspeed USB allows for data transfer rates ten times greater than that of USB 2.0. These robust cables provide a reliable interconnect from the camera to the computer. The thumbscrew locking feature meets the requirements of the soon to be released USB 3.0 Vision standard and insures a secure robust connection to the camera. Increased awg sizes allows for better performance over longer distance when compared to smaller awg cables.

Features – InfiniFlex

- Supports high data rate transfers up to 5 Gbps
- Robotic Grade – High Flex
- Thumbscrew locking
- Rugged overmolded interfaces

Cable Specifications – InfiniFlex

- Overall Diameter: .340 Inches
- Max Temperature: 80 Degrees C
- Jacket Color: Violet
- Min. Static Bend Radius: 3.4 Inches
- Min. Dynamic Bend Radius: 5.10 Inches
- Super Speed Pair: 26 awg
- UTP: 28 awg
- Power and Ground: 24 awg

Features – Static Grade

- Supports high data rate transfers of up to 5 Gbps
- Low cost USB 3.0
- Thumbscrew locking
- Overmolded interfaces

Cable Specifications – Static Grade

- Overall Diameter: .240 Inches
- Max Temperature: 60 Degrees C
- Jacket Color: Black
- UL Rated: UL 2725
- Min. Bend Radius: 2.4 Inches (Static)
- Flame Rating: VW-1