

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

AUTOVIMATION ORCA ENCLOSURES

22.941.180

Orca M, 2" lid, rear wall C (29x<80mm)



- Robust enclosure, max. camera size 62x62mm
- Maximum lens diameter 85mm in profile, 78mm in front lid
- Inner length 130mm (S), 180mm (M), 250mm (L) and 335mm (XL)
- Excellent heat dissipation, IP67 rated
- Wide selection of accessories available for mounting and maintenance



PRODUCT DESCRIPTION

Enclosure Configurator

The IP67 Orca enclosure series offers protection for larger cameras of up to 62 x 62mm cross section (for instance Sick Ranger, AVT Prosilica range, Basler Runner, Flir A300 etc.). Smaller cameras also fit into the Orca with special adapter plates, if a large ring light or lens requires more room. It is available in three standard length with different rear walls and front lids. Equipped with the larger 3" window and 65mm aperture diameter it is possible to use wide-angle lenses without obstruction. Even fish-eye lenses with more than 180° viewing angle can be used with the dome lid.

autoVimation offers a wide selection of enclosures to suit even the most specific requirements. To find a suitable enclosure please see the Enclosure Configurator (link above) or contact OEM Finland sales team for additional info!.



Order Numbers (please specify the camera type for each order!):

Product ID	Camera Height (cm)	Enclosure ID	2" Window Rear	Wall Type 3" Window	Length
2	standard: 4.0 - 6.2 <4.0 add surcharge 20.040.001	4	A: 0 C: 1 D: 2	A: 5 C: 6 D: 9	S: 130 M: 180 L: 250 XL: 335


TECHNICAL DATA

Height	96 mm
Housing material	Anodised aluminum
Inner length	180 mm
IP class	IP67
Length	194 mm
Max camera height	62 mm

Max camera width	62 mm
Max connector size	26.5 mm
Max lens diameter	85 mm
Weight	1200 g
Width	96 mm
Window seal	EPDM



Product	Image	Order No.	Product	Image	Order No.	Product	Image	Order No.
Air Nozzle	-	50.100.025	Position Ring	0	20.040.002	Mounting Kit 1	8	5.010.000
2" Wind Curtain	0	50.100.010	Cooling Module	1	60.100.010	Mounting Kit 2	4	5.020.000
Tube Wind Curtain 2*	0	50.100.017	El. Heating Plate	9	70.100.010	Mounting Kit 6	1	5.060.000
3" Wind Curtain	0	50.100.011	Sun roof Size S	-	20.011.001	Mounting Kit 7	=	5.070.000
Shutter 2" Shutter 3"	-	50.200.020 50.200.021	Size M Size L		20.011.002 20.011.003	Mounting Kit 9	3	5.090.000
Dome Window	(20.040.015	Rear Wall E	0	20.040.014	Mounting Kit 10	0	5.100.000
30mm Extension	1	15.030.030	Deflection Mirror 90°	6	20.020.004	Mounting Kit 15	4	5.150.000
60mm Extension	8	15.030.085	Corrugated Tube 28mm		20.000.006	Mounting Kit 16	Z	5.160.000
M72 Front Lid	0	20.040.018	Mounting Tool	1	90.000.004	Mounting Kit 17	20	5.170.000





2" Lid	3" Lid Dome Lid I	rofile S Profi	le M Profile L	RearWall A RearV	Vall C RearWall D	RearWal
	Camera Height (cm)			rder!): Rear Wall Type	3" Window	Length
2	standard; 4.0 - 6.2 c4.0 add surcharge 20.040.001	4	A: 0 C: 1 D: 2		A: 5 C: 6 D: 9	S: 130 M: 180 L: 250 XL: 335

Product	Image	Order No.	Product	Image	Order No.	Product	Image	Order No.
Air Nozzle	-	50.100.025	Position Ring	0	20.040.002	Mounting Kit 1	8	5.010.000
2" Wind Curtain	0	50.100.010	Cooling Module	-	60.100.010	Mounting Kit 2	4	5.020.000
Tube Wind Curtain 2"	0	50.100.017	El. Heating Plate	1	70.100.010	Mounting Kit 6	1	5.060.000
3" Wind Curtain	0	50.100.011	Sun roof Size S	10	20.011.001	Mounting Kit 7	=	5.070.000
Shutter 2" Shutter 3"	-	50.200.020 50.200.021	Size M Size L		20.011.002	Mounting Kit 9	3	5.090.000
Dome Window	(20.040.015	Rear Wall E	0	20.040.014	Mounting Kit 10	0	5.100.000
30mm Extension	1	15.030.030	Deflection Mirror 90°	6	20.020.004	Mounting Kit 15	4	5.150.000
60mm Extension	8	15.030.085	Corrugated Tube 28mm		20.000.006	Mounting Kit 16	Z	5.160.000
M72 Front Lid	0	20.040.018	Mounting Tool	6	90.000.004	Mounting Kit 17	ě	5.170.000

