

AUTOVIMATION ELEFANT ENCLOSURES

AutoVimation Enclosures For Industrial Cameras

2X.X26.141

Enclosure with 3" Flange + Cooling - Please contact vision@oem.co.uk to specify product code



- Robust construction
- IP66/IP67 Rating
- 90° Image Rotation
- Excellent Heat Dissipation

PRODUCT DESCRIPTION

SUITABLE FOR CAMERAS:

*The Elephant enclosure is also suitable for all smaller cameras that are not listed here.

- Adimec Diamond, Sapphire, Quartz
- Aida UHD6G-X12L
- AOS J-PRI, L-PRI, M-PRI
- AVMATRIX Eagle T10
- AVT Goldeye XSWIR
- Basler Boost
- Blue Vision BVC 3xxx/6xxx
- Bresser MikroCam PRO
- BZB Gear Maestro, Packshot C10X
- Canon ML-100, ML-105
- Chromasens allPIXA, chromaPIXA
- Crevis HX, LV
- CIS VCC-127CXP, VCC-250CXP
- Dalsa Linea 4K/8K/16K, Piranha4
- Fluke ThermoView TV40
- Freely Ember
- Hamamatsu Orca Fire/Flash, TDI
- HAIP BlackIndustry NIR/VNIR V2
- HIK MV-CL084-91GM
- HinaLea 4400 SWIR
- Illunis CMV
- IOI Flare CL12MP/CX
- iRayple Line Scan Cameras 8K
- ISVI IC-X25B-CL
- IX Cameras i-SPEED 211
- Jai Sweep 3-Sensor/4-Sensor, Wave
- Jenoptik Blackbird Precision, IR-TCM
- Lumenera Lg11059
- Mikrotrotron Eosens
- Novitec i-Nova3 Zoom
- OPT F-Mount cameras
- OptiTrack Primex 13
- Optronis CamPerform CP
- Optronis CamRecord Runner/Sprinter
- Phantom S200, S210
- Photonfocus MV-8
- Sierra-Olympia VAYU HD-I
- SmartMore SMI-C10GiL-8K-01M
- SVS Vistek SHR
- Vieworks VT
- Z CAM E2

And many more!

