

SCREW ON SHIELD CLIPS SSAB

SSAB

3694.0

SSAB 5, Screw down shield clip, 2 - 5mmØ cables,
Busbar mount

- Screw on clip for simple fitting
- Knurled thumbscrew, no tools required
- Large shield contact area



PRODUCT DESCRIPTION

The SSAB can be mounted on a busbar. After wiring the terminal block, the shield-connection clip is mounted by simply swivelling in and tightening the knurled thumb screw.

This makes the SSAB screw-shield-connection clip very convenient and quick to wire. Depending on the length of the terminal blocks, two or more SH/SAB busbar supports can be used. These mechanically connect the front busbar with the DIN rail (support).

The SH1 busbar supports are used where a shield-connection system requires to be mounted directly onto a panel rather than a DIN rail.

The 10 x 3 busbars can be easily and quickly snapped on to these supports. In both cases, the contact with the earth or ground potential can be established with a ZB clamping yoke.

TECHNICAL DATA

GENERAL DATA

| | |
|--------------------|---------|
| Cable diameter min | 2 mm |
| Cable diameter max | 5 mm |
| Mounting | Busbar |
| Colour | Natural |

DIMENSIONS

| | |
|--------|---------|
| Height | 46.8 mm |
| Length | 19.5 mm |
| Width | 9 mm |

ADDITIONAL DATA

| | |
|-------------------|----------|
| Tariff code | 85369010 |
| Country of origin | CN |
| Weight | 13.76 g |
| Pack size | 10 |
| Material | Steel |