OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SCREW ON SHIELD CLIPS SSAB

SSAB

3695.0
SSAB 8, Screw down shield clip, 3 - 8mmø cables, Busbar mount



- Screw on clip for simple fitting
- Knurled thumbscrew, no tools required
- Large shield contact area

PRODUCT DESCRIPTION

The SSAB can be mounted on a busbar. After wiring the terminal block, the shield-connection clip is mounted by simply swivelling in and tightening the knurled thumb screw.

This makes the SSAB screw-shield-connection clip very convenient and quick to wire. Depending on the length of the terminal blocks, two or more SH/SAB busbar supports can be used. These mechanically connect the front busbar with the DIN rail (support).

The SH1 busbar supports are used where a shield-connection system requires tot be mounted directly onto a panel rather than a DIN rail.

The 10 x 3 busbars can be easily and quickly snapped on to these supports. In both cases, the contact with the earth or ground potential can be established with a ZB clamping yoke.

TECHNICAL DATA

GENERAL DATA

Cable diameter min	3 mm
Cable diameter max	8 mm
Mounting	Busbar
Colour	Natural

DIMENSIONS

Height	48.7 mm
Length	19.5 mm
Width	12 mm

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	15.16 g
Pack size	10

Material	Steel