OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SCREW ON SHIELD CLIPS SSAB

SSAB

3699.0
SSAB 35, Screw down shield clip, 20 - 35mmø cables, Busbar mount



- Screw on clip for simple fitting
- Knurled thumbscrew, no tools required
- Large shield contact area

PRODUCT DESCRIPTION

The SSAB can be mounted on a busbar. After wiring the terminal block, the shield-connection clip is mounted by simply swivelling in and tightening the knurled thumb screw.

This makes the SSAB screw-shield-connection clip very convenient and quick to wire. Depending on the length of the terminal blocks, two or more SH/SAB busbar supports can be used. These mechanically connect the front busbar with the DIN rail (support).

The SH1 busbar supports are used where a shield-connection system requires tot be mounted directly onto a panel rather than a DIN rail.

The 10 x 3 busbars can be easily and quickly snapped on to these supports. In both cases, the contact with the earth or ground potential can be established with a ZB clamping yoke.

TECHNICAL DATA

GENERAL DATA

Cable diameter min	20 mm
Cable diameter max	35 mm
Mounting	Busbar
Colour	Natural

DIMENSIONS

Height	160.5 mm
Length	20 mm
Width	40 mm

ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	64.62 g
Pack size	10

Material	Steel