

## CABLE MARKER SLEEVES AND INSERTS

KH, ESS

4912.0

KH 30/12, Soft cable marker sleeve, 70mm<sup>2</sup> Soft cables, 12mm long

- for 0.25mm<sup>2</sup> to 70mm<sup>2</sup> cables
- Plottable polyamide inserts
- Halogen free options
- Yellow & transparent variants
- Coloured marker inserts



### PRODUCT DESCRIPTION

The KH range of cable marker sleeves, used in combination with the ESS Maxicard, enable cables to be labelled quickly and conveniently.

The sleeve is made easier to attach to the wire because of the special bellows shape construction of the cable marker sleeve.

When used together, the MCESS and the KH cable marker sleeves ensure that your labels are protected from the environment and the oval-shaped pocket makes the labels easy to insert before or after installation.

Can be used for marking wires from 0.25mm<sup>2</sup> up to 70 mm<sup>2</sup> and are available in five different lengths and six wire diameters.

Material: KH, Soft PVC, no cadmium or silicone – Resistant to Oil, benzene, gamma and UV radiation.

Material: KHZ, Soft PVC, no cadmium, halogen or silicone– Resistant to Oil, benzene, gamma and UV radiation.

Material: KH E, PVC – Resistant to Alkaline substances, alcohol and various cleaning agents.

### TECHNICAL DATA

<b>Additional information</b>	for conductor cross-section 16,0-70,0 mm <sup>2</sup>
<b>Cadmium free</b>	Yes
<b>Chemical resistant</b>	Yes
<b>Country of origin</b>	SE
<b>Flammability class</b>	UL94-V0
<b>Height</b>	19 mm
<b>Length</b>	12 mm
<b>Material</b>	PVC-P
<b>Operating temperature from</b>	-30 °C

Operating temperature to	60 °C
Outer insulation diameter max	16 mm
Outer insulation diameter min	8 mm
Pack size	50
Rated wire cross section from (AWG)	5
Rated wire cross section to (AWG)	3/0
Silicone-free	Yes
Tariff code	39269097
UV-resistant	Yes
Weight	1 g
Width	10 mm
Wire cross section min	16 mm <sup>2</sup>
Wire cross-section max	70 mm <sup>2</sup>