

## CABLE MARKER SLEEVES 1.5MM<sup>2</sup> TO 4MM<sup>2</sup>

KBH 5

2160.0324

KBH 5/3 Printed "y", Roll of 1000

- for 1.5mm<sup>2</sup> to 4mm<sup>2</sup> cable range
- Available in yellow or industry standard colours
- bags or rolls
- Pre-printed or blanks



### PRODUCT DESCRIPTION

The KBH cable marker sleeves provide a safe, quick and simple solution for marking unconnected cables.

Perfect for use with wire cross-sections from 1.5 to 4 mm<sup>2</sup>, available in 3 mm and 6 mm lengths.

Easy to read with high-contrast print.

### TECHNICAL DATA

|                                 |         |
|---------------------------------|---------|
| Cadmium free                    | Yes     |
| Chemical resistant              | Yes     |
| Colour                          | Yellow  |
| Country of origin               | SE      |
| Flammability class              | UL94-V0 |
| Height                          | 5.5 mm  |
| Length                          | 3 mm    |
| Material                        | PVC-P   |
| Number of characters per sleeve | 1       |
| Operating temperature from      | -30 °C  |
| Operating temperature to        | 60 °C   |
| Outer insulation diameter max   | 5 mm    |
| Outer insulation diameter min   | 2.5 mm  |
| Pack size                       | 1000    |

|  |                     |
|--|---------------------|
| <b>Print colour</b>                        | Black               |
| <b>Printing process</b>                    | Hot stamping        |
| <b>Rated wire cross section from (AWG)</b> | 16                  |
| <b>Rated wire cross section to (AWG)</b>   | 11                  |
| <b>Silicone-free</b>                       | Yes                 |
| <b>Tariff code</b>                         | 49119900            |
| <b>Text height</b>                         | 2.6 mm              |
| <b>UV-resistant</b>                        | Yes                 |
| <b>Weight</b>                              | 0.05 g              |
| <b>Width</b>                               | 4.2 mm              |
| <b>Wire cross section min</b>              | 1.5 mm <sup>2</sup> |
| <b>Wire cross-section max</b>              | 4 mm <sup>2</sup>   |