

## CABLE MARKER SLEEVES FOR 0.2MM<sup>2</sup> TO 1.5MM<sup>2</sup>

KBH 3

2631.0102

KBH 3/3 Blank Red, Bags of 200

- for 0.2mm<sup>2</sup> to 1.5mm<sup>2</sup> cable range
- Available in yellow or industry standard colours
- Bags or rolls
- Pre-printed or blanks



### PRODUCT DESCRIPTION

KBH cable marker sleeves provide a safe, quick and simple marking solution.

Safe and adjustable, for unconnected cables. Perfect for use with wire cross-sections of 0.2 through to 70mm<sup>2</sup>. Available in 3mm, 4mm and 6mm lengths. Easy to read with a high-contrast typeface. Torsion resistant for reliable marking combinations.

Material: Soft PVC, with no cadmium or silicone.

### TECHNICAL DATA

|                                 |              |
|---------------------------------|--------------|
| Cadmium free                    | Yes          |
| Chemical resistant              | Yes          |
| Colour                          | Red          |
| Country of origin               | SE           |
| Flammability class              | UL94-V0      |
| Height                          | 3.6 mm       |
| Length                          | 3 mm         |
| Material                        | PVC-P        |
| Number of characters per sleeve | 1            |
| Operating temperature from      | -30 °C       |
| Operating temperature to        | 60 °C        |
| Outer insulation diameter max   | 3 mm         |
| Outer insulation diameter min   | 1.3 mm       |
| Pack size                       | 200          |
| Printing process                | Hot stamping |

|  |                     |
|--|---------------------|
| <b>Rated wire cross section from (AWG)</b> | 24                  |
| <b>Rated wire cross section to (AWG)</b>   | 16                  |
| <b>Silicone-free</b>                       | Yes                 |
| <b>Tariff code</b>                         | 39269097            |
| <b>Text height</b>                         | 2.6 mm              |
| <b>UV-resistant</b>                        | Yes                 |
| <b>Weight</b>                              | 0.04 g              |
| <b>Width</b>                               | 3.5 mm              |
| <b>Wire cross section min</b>              | 0.2 mm <sup>2</sup> |
| <b>Wire cross-section max</b>              | 1.5 mm <sup>2</sup> |