

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **CABLE MARKER SLEEVE FOR 70MM² AND ABOVE**

KBH-S4

2671.0109 KBH-S 4 Blank White, Roll of 500

- Use with KH holders and ties
- unlimited combinations
- bags or rolls
- Pre-printed or blanks
- Soft PVC, cadmium & silicone free



**■**CONTACLIP

## PRODUCT DESCRIPTION

The KBH-S cable marker sleeves provide a safe, quick and simple solution for marking cables with wire cross-sections of 70 mm² and larger. Quick assembly using with KH holders and cable ties.

## **TECHNICAL DATA**

Cadmium freeYesChemical resistantYesColourWhiteCountry of originSEFlammability classUL94-V0Length4 mmMaterialPVC-PNumber of characters per sleeve1Operating temperature from-30 °COperating temperature to60 °COuter insulation diameter max16 mmPack size500Printing processHot stamping		
Colour Country of origin SE Flammability class UL94-V0 Length 4 mm Material PVC-P Number of characters per sleeve 1 Operating temperature from -30 °C Operating temperature to 60 °C Outer insulation diameter max 16 mm Pack size 500	Cadmium free Yes	
Country of origin  Flammability class  UL94-V0  Length  4 mm  Material  PVC-P  Number of characters per sleeve  1  Operating temperature from  -30 °C  Operating temperature to  60 °C  Outer insulation diameter max  16 mm  Pack size  500	Chemical resistant Yes	
Flammability classUL94-V0Length4 mmMaterialPVC-PNumber of characters per sleeve1Operating temperature from-30 °COperating temperature to60 °COuter insulation diameter max16 mmPack size500	<b>Colour</b> White	
Length 4 mm  Material PVC-P  Number of characters per sleeve 1  Operating temperature from -30 °C  Operating temperature to 60 °C  Outer insulation diameter max 16 mm  Pack size 500	Country of origin SE	
MaterialPVC-PNumber of characters per sleeve1Operating temperature from-30 °COperating temperature to60 °COuter insulation diameter max16 mmPack size500	Flammability class UL94-V0	
Number of characters per sleeve 1  Operating temperature from -30 °C  Operating temperature to 60 °C  Outer insulation diameter max 16 mm  Pack size 500	Length 4 mm	
Operating temperature from -30 °C Operating temperature to 60 °C Outer insulation diameter max 16 mm Pack size 500	Material PVC-P	
Operating temperature to 60 °C  Outer insulation diameter max 16 mm  Pack size 500	Number of characters per sleeve 1	
Outer insulation diameter max 16 mm  Pack size 500	Operating temperature from -30 °C	
Pack size 500	Operating temperature to 60 °C	
	Outer insulation diameter max 16 mm	
Printing process Hot stamping	Pack size 500	
	Printing process Hot stamping	

Rated wire cross section to (AWG)	3/0
Silicone-free	Yes
Tariff code	39269097
UV-resistant	Yes
Weight	0.12 g
Wire cross-section max	70 mm²