0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

■CONTACLIP

CABLE MARKER SLEEVE FOR 70MM² AND ABOVE

KBH-S4

2671.0107 KBH-S 4 Blank Violet/White, Roll of 500

- Use with KH holders and ties
- unlimited combinations
- bags or rolls
- Pre-printed or blanks
- Soft PVC, cadmium & silicone free



PRODUCT DESCRIPTION

The KBH-S cable marker sleeves provide a safe, quick and simple solution for marking cables with wire cross-sections of 70 mm² and larger. Quick assembly using with KH holders and cable ties.

TECHNICAL DATA

Cadmium freeYesChemical resistantYesColourVioletCountry of originSEFlammability classUL94-V0Length4 mmMaterialPVC-PNumber of characters per sleeve1Operating temperature from-30 °COperating temperature to60 °COuter insulation diameter max16 mmPack size500Printing processHot stamping		
Colour Country of origin SE Flammability class UL94-V0 Length 4 mm Material PVC-P Number of characters per sleeve 1 Operating temperature from -30 °C Operating temperature to 60 °C Outer insulation diameter max 16 mm Pack size SE	Cadmium free	Yes
Country of origin Flammability class UL94-V0 Length 4 mm Material PVC-P Number of characters per sleeve 1 Operating temperature from -30 °C Operating temperature to 60 °C Outer insulation diameter max 16 mm Pack size 500	Chemical resistant	Yes
Flammability classUL94-V0Length4 mmMaterialPVC-PNumber of characters per sleeve1Operating temperature from-30 °COperating temperature to60 °COuter insulation diameter max16 mmPack size500	Colour	Violet
Length 4 mm Material PVC-P Number of characters per sleeve 1 Operating temperature from -30 °C Operating temperature to 60 °C Outer insulation diameter max 16 mm Pack size 500	Country of origin	SE
MaterialPVC-PNumber of characters per sleeve1Operating temperature from-30 °COperating temperature to60 °COuter insulation diameter max16 mmPack size500	Flammability class	UL94-V0
Number of characters per sleeve 1 Operating temperature from -30 °C Operating temperature to 60 °C Outer insulation diameter max 16 mm Pack size 500	Length	4 mm
Operating temperature from -30 °C Operating temperature to 60 °C Outer insulation diameter max 16 mm Pack size 500	Material	PVC-P
Operating temperature to 60 °C Outer insulation diameter max 16 mm Pack size 500	Number of characters per sleeve	1
Outer insulation diameter max 16 mm Pack size 500	Operating temperature from	-30 °C
Pack size 500	Operating temperature to	60 °C
	Outer insulation diameter max	16 mm
Printing process Hot stamping	Pack size	500
	Printing process	Hot stamping

Rated wire cross section to (AWG)	3/0
Silicone-free	Yes
Tariff code	39269097
UV-resistant	Yes
Weight	0.12 g
Wire cross-section max	70 mm²