OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CABLE MARKER SLEEVES AND INSERTS

Cable Markers - KH, ESS

5993.0
KHZ 20/15, Soft HF cable marker sleeve, 16mm² cables, 15mm long



- for 0.25mm² to 70mm² cables
- Plottable polyamide inserts
- Halogen free options
- Yellow & transparent variants
- Coloured marker inserts

PRODUCT DESCRIPTION

The **KH range of** cable marker sleeves, used in combination with the **ESS Maxicard**, enable cables to be labelled quickly and conveniently.

The sleeve is made easier to attach to the wire because of the special bellows shape construction of the cable marker sleeve.
When used together, the **MCESS** and the **KH** cable marker sleeves ensure that your labels are protected from the environment and the oval-shaped pocket makes the labels easy to insert before or after installation.
Can be used for marking wires from 0.25mm² up to 70 mm² and are available in five different lengths and six wire diameters.

Material: KH, Soft PVC, no cadmium or silicone – Resistant to Oil, benzene, gamma and UV radiation.

Material: KHZ, Soft PVC, no cadmium, halogen or silicone– Resistant to Oil, benzene, gamma and UV radiation.

Material: KH E, PVC – Resistant to Alkaline substances, alcohol and various cleaning agents.

TECHNICAL DATA

Additional information	for conductor cross-section 2,5-16,0 mm²
Cadmium free	Yes
Chemical resistant	Yes
Colour	Yellow, Transparent
Country of origin	SE
Flammability class	UL94-V0
Halogen-free	Yes
Height	10 mm
Length	15 mm

Material	PVC-P
Operating temperature from	-30 °C
Operating temperature to	90 °C
Outer insulation diameter max	10 mm
Outer insulation diameter min	4 mm
Pack size	100
Rated wire cross section from (AWG)	13
Rated wire cross section to (AWG)	5
Silicone-free	Yes
Tariff code	39269097
UV-resistant	Yes
Weight	0.5 g
Width	6 mm
Wire cross section min	2.5 mm²
Wire cross-section max	16 mm²