

## *<b>ZCONTACLIP*

## **CABLE MARKER SLEEVES AND INSERTS**

KH, ESS

5995.0 KHZ 20/21, Soft HF cable marker sleeve, 16mm<sup>2</sup> cables, 21mm long

- for 0.25mm<sup>2</sup> to 70mm<sup>2</sup> cables
- Plottable polyamide inserts
- Halogen free options
- Yellow & transparent variants
- · Coloured marker inserts



## **PRODUCT DESCRIPTION**

The KH range of cable marker sleeves, used in combination with the ESS Maxicard, enable cables to be labelled quickly and conveniently.

The sleeve is made easier to attach to the wire because of the special bellows shape construction of the cable marker sleeve. When used together, the MCESS and the KH cable marker sleeves ensure that your labels are protected from the environment and the oval-shaped pocket makes the labels easy to insert before or after installation.

Can be used for marking wires from 0.25mm<sup>2</sup> up to 70 mm<sup>2</sup> and are available in five different lengths and six wire diameters.

Material: KH, Soft PVC, no cadmium or silicone - Resistant to Oil, benzene, gamma and UV radiation.

Material: KHZ, Soft PVC, no cadmium, halogen or silicone- Resistant to Oil, benzene, gamma and UV radiation.

Material: KH E, PVC - Resistant to Alkaline substances, alcohol and various cleaning agents.

## **TECHNICAL DATA**

Additional information	for conductor cross-section 2,5-16,0 mm <sup>2</sup>
Cadmium free	Yes
Chemical resistant	Yes
Colour	Yellow, Transparent
Country of origin	SE
Flammability class	UL94-V0
Halogen-free	Yes
Height	10 mm
Length	21 mm

Material	PVC-P
Operating temperature from	-30 °C
Operating temperature to	90 °C
Outer insulation diameter max	10 mm
Outer insulation diameter min	4 mm
Pack size	100
Rated wire cross section from (AWG)	13
Rated wire cross section to (AWG)	5
Silicone-free	Yes
Tariff code	39269097
UV-resistant	Yes
Weight	0.56 g
Width	6 mm
Wire cross section min	2.5 mm <sup>2</sup>
Wire cross-section max	16 mm²