**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# CABLE MARKER SLEEVES AND INSERTS

Cable Markers - KH, ESS

9384.0
KH E 25.0/30, HF Cable marker sleeve, 25mm² cables, 30mm long




- for 0.25mm² to 70mm² cables
- Plottable polyamide inserts
- Halogen free options
- Yellow & transparent variants
- Coloured marker inserts

**PRODUCT DESCRIPTION**

The **KH range of** cable marker sleeves, used in combination with the **ESS Maxicard**, enable cables to be labelled quickly and conveniently.

The sleeve is made easier to attach to the wire because of the special bellows shape construction of the cable marker sleeve.
When used together, the **MCESS** and the **KH** cable marker sleeves ensure that your labels are protected from the environment and the oval-shaped pocket makes the labels easy to insert before or after installation.
Can be used for marking wires from 0.25mm² up to 70 mm² and are available in five different lengths and six wire diameters.

Material: KH, Soft PVC, no cadmium or silicone – Resistant to Oil, benzene, gamma and UV radiation.

Material: KHZ, Soft PVC, no cadmium, halogen or silicone– Resistant to Oil, benzene, gamma and UV radiation.

Material: KH E, PVC – Resistant to Alkaline substances, alcohol and various cleaning agents.

# TECHNICAL DATA

| | |
|---|---|
| **Additional information** | for conductor cross-section 10,0-25,0 mm² |
| **Country of origin** | IT |
| **Flammability class** | UL94-V0 |
| **Halogen-free** | Yes |
| **Length** | 30 mm |
| **Material** | PVC |
| **Operating temperature from** | -40 °C |
| **Operating temperature to** | 90 °C |
| **Outer insulation diameter max** | 10 mm |

| | |
|---|---|
| **Outer insulation diameter min** | 6 mm |
| **Pack size** | 500 |
| **Tariff code** | 39162000 |
| **Weight** | 1.36 g |
| **Wire cross section min** | 10 mm² |
| **Wire cross-section max** | 25 mm² |