

## SNAP ON CABLE MARKERS

### KMC

9810.8

MC KMC 0/4x12/40 YE, 1mm<sup>2</sup> cable, 12 x 4.1mm  
markers - Yellow

- Can be fitted on terminated cables
- for 0.14mm<sup>2</sup> to 2.5mm<sup>2</sup> cables, 0.9mm to 3.5mm outer  $\phi$
- Custom Print available
- Compatible with EMS Plotter
- Halogen Free



### PRODUCT DESCRIPTION

The Maxicard KMC is a clear, quick and simple solution for making cables that have already been terminated.

The plastic halves snap together around the cable to hold the marker firmly on the cable.

The KMC 0 version is the most versatile, fitting cables from 0.14mm<sup>2</sup> to 1.0mm<sup>2</sup> cross-sections or cable diameter 0.9mm...2.6mm.

The KMC 1 version is designed for cables with a cross-section 0.75mm<sup>2</sup>...2.5mm<sup>2</sup> or cable diameter of 2.00mm...3.5mm.

They are available in three lengths - 12mm x 4.1mm, 21mm x 4.1mm and 30mm x 4.1mm.

OEM can custom print to your requirements, please contact for further information.

## TECHNICAL DATA

|                                        |                                                      |
|----------------------------------------|------------------------------------------------------|
| <b>Additional information</b>          | for conductor cross-section 0,14-1,0 mm <sup>2</sup> |
| <b>Colour</b>                          | Yellow                                               |
| <b>Country of origin</b>               | DE                                                   |
| <b>Flammability class</b>              | UL94-V2                                              |
| <b>Halogen-free</b>                    | Yes                                                  |
| <b>Length</b>                          | 12 mm                                                |
| <b>Marker material</b>                 | Polyamide 6.6                                        |
| <b>Number of characters horizontal</b> | 8                                                    |
| <b>Number of characters vertical</b>   | 2                                                    |
| <b>Number of markers per card</b>      | 40                                                   |
| <b>Number of markers per row</b>       | 5                                                    |

|                                                          |                      |
|----------------------------------------------------------|----------------------|
| <b>Operating temperature from</b>                        | -40 °C               |
| <b>Operating temperature to</b>                          | 105 °C               |
| <b>Outer insulation diameter max</b>                     | 2.6 mm               |
| <b>Outer insulation diameter min</b>                     | 0.9 mm               |
| <b>Pack size</b>                                         | 200                  |
| <b>Plotter inlay</b>                                     | CCI-10               |
| <b>Rows at font size 1.4 and pen 0.25mm horizontally</b> | 1                    |
| <b>Rows at font size 1.4 and pen 0.25mm vertically</b>   | 5                    |
| <b>Tariff code</b>                                       | 39269097             |
| <b>Weight</b>                                            | 0.35 g               |
| <b>Width</b>                                             | 4.1 mm               |
| <b>Wire cross section min</b>                            | 0.14 mm <sup>2</sup> |
| <b>Wire cross-section max</b>                            | 1 mm <sup>2</sup>    |