

**COMPACT LOOP HEATER 60 - 150W - LP
165**

LP

16501.0-00
LP 165, 60W Slim line loop heater, 110V-265V ac/dc

- Compact with small foot print
- DIN rail mount
- Wide voltage range
- PTC technology

PRODUCT DESCRIPTION

Compact Slim line PTC loop heater designed for continuous operation. The new loop design increases the efficiency of the chimney heating effect and has enabled the width to be reduced, saving space in the enclosures

TECHNICAL DATA**GENERAL DATA**

Heat output	60 W
Nominal voltage	120-240 V AC/DC
Heater body	Anodized aluminum
Mounting	DIN-rail 35mm
Connection type	3 pressure clamps for stranded wire 0.5-1.5mm ² and rigid wire 0.5- 2.5mm ²
Heat source	Self-regulating PTC-element
Starting current max	4 A
Recommended fuse (slow blow)	6 A

DIMENSIONS

Height	107 mm
Width	42 mm
Depth	121 mm
Weight	0.3 kg

SAFETY & APPROVALS




Protection class	I (earthed)
IP class	IP20


Approvals	RoHS 3, CE, UKCA, cRUus, EAC, UL E234324, VDE
-----------	---

RATED OPERATING CONDITIONS

Operational temperature	-45°C ... +70°C
Storage temperature	-45°C ... +70°C
Operating humidity	<90% RH
Humidity storage	<90% RH

Voltage min	110 V ac/dc
Voltage max	265 V ac/dc
Housing	Anodized aluminium





Example of connection

