

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

FAN HEATER 400-550 W CR027

02701.0-00 CR 027 550/650W Fan heater, 50/60Hz, 220-240V ac, 0...60°C

- · Integrated thermostat
- · Indication light on front
- Modern design





PRODUCT DESCRIPTION

The heat source in this fan is a PTC element – a semiconductor that adapts its output to the ambient temperature. The colder it is, the more heat it produces. The PTC element has a high starting current and provides full output almost immediately.

The fan has an integrated adjustable thermostat, and can for example, be installed in enclosures indoors or outdoors to maintain an even temperature and thus avoid condensation, or it can be used to assure that the temperature is kept above a lowest permitted level.

The CR 027 is designed to be clip in to din rail

TECHNICAL DATA

GENERAL DATA

| Heat output | 550 W |
|------------------|--|
| Nominal voltage | 230 V AC |
| Frequency | 50/60 Hz |
| Heater body | Plastic |
| Material of body | Plastic |
| Mounting | Clip on, DIN rail |
| Colour | Light grey |
| Number of fans | 1 |
| Connection type | 2-pole terminal for 2.5 mm ² cable. Tightening torque for connection screws max. 0.8 Nm |

| Heat source | Self-regulating PTC-element |
|------------------------------|-----------------------------|
| Recommended fuse (slow blow) | 10 A |
| Inrush max | 13 A |
| Life span | 50 000 h @ +25 °C |
| Air capacity | 45 m³/h |
| DIMENSIONS | |
| Height | 165 mm |
| Width | 100 mm |
| Depth | 128 mm |
| Weight | 1.1 kg |

SAFETY & APPROVALS

Behind panel depth

| Protection class | II (double insulated) |
|------------------------|--|
| IP class | IP20 |
| Approvals | CE, cULus, EAC, RoHS, UL, VDE |
| Flammability class | UL94-V0 |
| Overheating protection | Overheat protection, fan failure with auto-reset |

128 mm

RATED OPERATING CONDITIONS

| Operational temperature | -45°C +70°C |
|--------------------------------|-------------------------|
| Storage temperature | -45°C +70°C |
| Operating humidity | < 90% RH |
| Humidity storage | <90% RH |
| Hysteresis temperature | 7К |
| Control range temperature from | 0 °C |
| Control range temperature to | 60 °C |
| | |
| Voltage min | 220 V ac |
| Voltage max | 240 V ac |
| Fan | Axial fan, ball bearing |
| Material plastic housing | Plastic |

