

C4 INDUSTRIAL RELAY

4-pole 10 A - MRC

C4-R3024D

Relay 14 Pin 3 Pole Latching 24V dc

- Marking system that can be custom-marked at factory
- Colour-coded test button, both lockable and spring-loaded
- Mechanical indication, double windows



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Nominal power dc	1.5 W
Coil voltage dc	24 V DC

OUTPUT DATA

Number of contacts	3
Contact material	AgNi
Breaking Voltage	250 V
Breaking capacity current	10 A
Recommended max load	10 A/250 V AC-1; 0,5 A/110 V DC-1
Recommended min load	10 mA/10 V; 5 mA/5 V
Resistive load 110 V dc max	55 W
Resistive load 24 V dc max	240 W
Surge current (20 ms)	30 A

GENERAL DATA

IP class	IP40
Isolation contact/contact	2500 V
Isolation contact/coil	2500 V

Insulation class EN60947	250 V Pollution 3, Group C
--------------------------	----------------------------

Temperature operational min	-40 °C
-----------------------------	--------

Storage temperature min	-40 °C
-------------------------	--------

Storage temperature max	80 °C
-------------------------	-------

Temperature operational max	60 °C
-----------------------------	-------

Frequency	50 Hz
-----------	-------

Optional coil	Bistable
---------------	----------

Weight	95 g
--------	------

Approvals	CCC, Gost R, CE, RoHS
-----------	-----------------------

