OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

C5 INDUSTRIAL RELAY

3-pole 16 A - MRC

C5-R20230A
Relay 11 Pin 2 Pole 16A Latching 230V ac



- Marking system
- Colour-coded test button, both lockable and non-lockable
- Mechanical indication, double windows

PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Coil voltage ac	230 V AC

OUTPUT DATA

Number of contacts	2
Contact material	AgNi
Nominal current	10 A
Breaking Voltage	400 V
Breaking capacity current	10 A
Recommended max load	10 A/400 V AC-1; 0,5 A/110 V DC-1
Resistive load 110 V dc max	55 W
Resistive load 24 V dc max	240 W
Surge current (20 ms)	30 A

GENERAL DATA

IP class	IP40
Isolation contact/contact	4000 V
Isolation contact/coil	4000 V
Insulation class EN60947	500 V, Pullution 3, Group C
Temperature operational min	-40 °C
Storage temperature min	-40 °C

Storage temperature max	80 °C
Temperature operational max	60 °C
Frequency	50 Hz
Optional coil	Bistable
Weight	95 g

