

C12 INTERFACE RELAY

2-pole 5 A - IRC

C12G22FX24D

Relay 6 Pin 2 Pole N/O Diode LED 24V dc

- Robust flat pins
- Both mechanical and LED indication
- Colour-coded test button
- Integrated safety components



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Working Un	0,8-1,10
Nominal power dc	0.7 W
Coil voltage dc	24 V DC
Voltage min	0.35 V
Overvoltage UNX max	1.1
Response time	10 ms

OUTPUT DATA


Number of contacts	2
Contact material	AgNi + 3 µ Au
Breaking Voltage	250 V
Breaking capacity current	5 A
Recommended max load	5 A/250 V AC 1; 0,5A/110 V DC-1
Recommended min load	5 mA/5 V
Mechanical life expectancy	AC: 10Mill/. DC: 20 Mill
Surge current (20 ms)	15 A
Bounce time	1
Release time	5 ms

Release time + contact debounce	8 ms
---------------------------------	------

GENERAL DATA

IP class	IP40
Isolation contact/contact	3000 V
Isolation contact/coil	5000 V
Frequency	50 Hz
Optional coil	FX (pole protection + LED)
Weight	21 g


Gap:
1 mm



C12-G22FX



5A 250V AC-1

5A 30V DC-1



-A2 -A1+

02



CE EAC

Made in India

