

## C4 INDUSTRIAL RELAY

4-pole 10 A - MRC

C4-X20X110D

Relay 14 Pin 2 Pole N/O 3mm GAP LED 110V dc

- Marking system that can be custom-marked at factory
- Colour-coded test button, both lockable and spring-loaded
- Mechanical indication, double windows



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### INPUT DATA

|                  |          |
|------------------|----------|
| Nominal power dc | 1.3 W    |
| Coil voltage dc  | 110 V DC |

#### OUTPUT DATA

|                           |       |
|---------------------------|-------|
| Number of contacts        | 2     |
| Contact material          | AgNi  |
| Breaking Voltage          | 250 V |
| Breaking capacity current | 10 A  |
| Surge current (20 ms)     | 30 A  |
| Release time              | 8 ms  |

#### GENERAL DATA

|                             |        |
|-----------------------------|--------|
| IP class                    | IP40   |
| Isolation contact/contact   | 2500 V |
| Isolation contact/coil      | 2500 V |
| Temperature operational min | -40 °C |
| Storage temperature min     | -40 °C |
| Storage temperature max     | 80 °C  |

|                             |               |
|-----------------------------|---------------|
| Temperature operational max | 60 °C         |
| Frequency                   | 50 Hz         |
| Optional coil               | X (LED)       |
| Weight                      | 90 g          |
| Approvals                   | CCC, CE, RoHS |

