

C5 INDUSTRIAL RELAY

3-pole 16 A - MRC

C5-M10X110D

Relay 11 Pin 1 Pole 16A BM LED 110V dc

- Marking system
- Colour-coded test button, both lockable and non-lockable
- Mechanical indication, double windows



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Working Un	0,80-1,10
Nominal power dc	1.3 W
Coil voltage dc	110 V DC

OUTPUT DATA

Number of contacts	1
Contact material	AgNi
Nominal current	16 A
Breaking Voltage	400 V
Breaking capacity current	16 A
Recommended max load	16 A/400 V AC-1; 3,6 A/110 V DC-13
Surge current (20 ms)	40 A
Bounce time	3
Release time + contact debounce	11 ms

GENERAL DATA

IP class	IP40
Isolation contact/contact	4000 V
Isolation contact/coil	4000 V

Insulation class EN60947	500 V, Pollution 3, Group C
Temperature operational min	-40 °C
Storage temperature min	-40 °C
Storage temperature max	80 °C
Temperature operational max	60 °C
Frequency	50 Hz
Optional coil	X (LED)
Weight	90 g
Approvals	CE, UL, RoHS, CSA, Gost R

