OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CHI14-34 HIGH INRUSH POWER RELAY

CHI34/UC24-240V
Power Relay 16A High Inrush 800A 24-240V ac/dc 3-Pole



- Inrush current up to 800 A
- Suitable for latest generation energy lamps and LED
- Rated current 16 A
- Extremely low operation noise

PRODUCT DESCRIPTION

The CHI is a power relay for all applications effecting high inrush currents up to 800 A such as electronic control gears of energy saving lamps, power supplies of the latest LED lights and switching supplies of industrial components. These loads show an inrush current up to 250 times of their nominal current.
The CHI14 is equiped with a single low noise operating NO contact with nominal current up to 16 A with installation width of 17.5mm. CHI34 has 3 NO and an auxiliary contact and a manual on-auto-off actuator.

TECHNICAL DATA

Working Un	16,8...250 V

Number of contacts	3
Breaking Voltage	250 V
Recommended min load	100 mA /12 V

Width	36 mm
Approvals	CE, RoHS, UL
IP class	IP20
Temperature operational min	-40 °C
Temperature operational max	60 °C
Storage temperature min	-40 °C
Storage temperature max	85 °C
Weight	125 g
Material	Lexan

Switching capacity AC1	4000 VA
Breaking capacity DC1	384 W
Power consumption	30 VA / 30 mW
Torque connection	0.6
2421_Peak current (A)	800 / 200µs
Voltage range	24-240 V AC/DC
Surge current (20 ms)	165 A
Connection area multiple conductors	2,5mm2/2x1,5mm2
Nominal current	16 A

















