OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# C4 INDUSTRIAL RELAY

4-pole 10 A - MRC

C4-X20X24D
Relay 14 Pin 2 Pole N/O 3mm GAP LED 24V dc



- Marking system that can be custom-marked at factory
- Colour-coded test button, both lockable and spring-loaded
- Mechanical indication, double windows

**PRODUCT DESCRIPTION**

# TECHNICAL DATA

## INPUT DATA

| | |
|---|---|
| **Nominal power dc** | 1.3 W |
| **Coil voltage dc** | 24 V DC |

## OUTPUT DATA

| | |
|---|---|
| **Number of contacts** | 2 |
| **Contact material** | AgNi |
| **Breaking Voltage** | 250 V |
| **Breaking capacity current** | 10 A |
| **Surge current (20 ms)** | 30 A |
| **Release time** | 8 ms |

## GENERAL DATA

| | |
|---|---|
| **IP class** | IP40 |
| **Isolation contact/contact** | 2500 V |
| **Isolation contact/coil** | 2500 V |
| **Temperature operational min** | -40 °C |
| **Storage temperature min** | -40 °C |
| **Storage temperature max** | 80 °C |
| **Temperature operational max** | 60 °C |

| | |
|---|---|
| **Frequency** | 50 Hz |
| **Optional coil** | X (LED) |
| **Weight** | 90 g |
| **Approvals** | CCC, CE, RoHS |

