
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# INTERFACE RELAY BASES ONLY

16190.2
IRC 6...12...24V AC/DC, Relay base




- Mount/dismount lever
- Pluggable external cross-connectors

**PRODUCT DESCRIPTION**

# TECHNICAL DATA

## INPUT DATA

| | |
|---|---|
| **Rated voltage Un** | 6-12-24 V ac/dc |
| **Overvoltage category** | III |
| **Contamination degree** | 3 |
| **LED status** | Yes |

## OUTPUT DATA

| | |
|---|---|
| **Contact configuration** | 1 CO |
| **Rated V ac / switching V ac max** | 250 / 400 V ac |

## CONNECTION DATA

| | |
|---|---|
| **Cross section single wire from** | 0.2 mm² |
| **Cross section single wire to** | 2.5 mm² |
| **Stripping length** | 10 mm |
| **Torque** | 0.5 |
| **Connection type** | Screw |

## GENERAL DATA

| | |
|---|---|
| **Approvals** | CE |
| **IP class** | IP20 |
| **Operating temperature from** | -40 °C |
| **Operating temperature to** | 70 °C |

## DIMENSIONS & MATERIALS

| | |
|---|---|
| **Width** | 6.2 mm |
| **Length** | 87 mm |
| **Height TS 35 / 7.5 with base** | 90.7 mm |
| **Flammability class** | UL94-V2 |

## ADDITIONAL DATA

| | |
|---|---|
| **Tariff code** | 85369010 |
| **Country of origin** | EEC |
| **Weight** | 32.7 g |
| **Pack size** | 10 |